



**EAGLE TUGS**  
26111 Northline Rd  
Taylor, MI 48180  
800 671 0431 tel  
734 442 1000 tel  
734 442 1005 fax  
www.eagletugs.com

# EAGLE BOB TAIL® TOW TRACTOR

## EB2-10

In 1969, the genesis of today's air cargo industry occurred. Eagle was there to answer the airlines call for an all-weather, high speed cargo tractor which had not yet been invented. Eagle successfully engineered and developed the Ford F-350 Bob Tail for United Airlines at Detroit Metropolitan Airport. Within two decades, the Eagle Bob Tail had become the narrow and wide body cargo towing standard used by all North American and British Airlines, and also military GSE. Eagle experienced reduced Bob Tail interest in the mid 1990's as its customers tried industrial tractors, converted to high speed use, as Bob Tail replacements. However, by 2003 the converted industrial tractors had demonstrated a track record of unreliability when compared to the Eagle Bob Tail. Examples of these problems include drive shaft, drive wheel, drive hub and braking issues. Other known issues included exhaust in the cab, and excessive driver fatigue and discomfort caused by a lack of suspension. Because of these problems, Eagle Bob Tail customers have returned with increased annual purchases.

### What the Eagle Bob Tail cargo tractor offers that industrial tractors do not:

- Eagle Tugs was the originator of the Bob Tail design over 40 years ago.
- The Ford F-750 Cab and Chassis have an unequalled commercially-proven, reliable drive train and braking system.
- Ford cabs are ergonomic, comfortable and safe.
- Rear Hitch sight tunnel.
- Heavy steel plate body and front & rear bumpers, including a heavy tubular grill guard and side protection.
- Unparalleled reliability and factory-direct support is the Eagle Tugs advantage.



### STANDARD FEATURES

Speed governed to 25 MPH  
Rear hitch sight tunnel  
Turn, stop, tail and backup lights on cab protection rack  
Air Conditioning  
Power steering & braking (hydraulic)  
Ventilated front and rear disc brakes  
Heavy duty wheels and radial tires

### RECOMMENDED OPTIONS

Limited slip differential  
E-hitch or Pintle Hook on rear and/or front of tractor  
Brake pedal safety pad  
Beacon or strobe  
De-activated door locks  
Sliding rear window

### TOWING CAPACITY

**EB2-10**  
Ford F-750 / \*60,000 lbs / 27,273 kg

\*Towing capacity shown as high speed towing @ 25 mph.



**EAGLE TUGS**  
 26111 Northline Rd  
 Taylor, MI 48180  
 800 671 0431 tel  
 734 442 1000 tel  
 734 442 1005 fax  
 www.eagletugs.com

## EAGLE BOB TAIL® TOW TRACTOR

	MODELS	EB2-10
PERFORMANCE	Drive Wheels	4 Rear
	Drawbar Pull Gas	
	Drawbar Pull Diesel	10,000 lbf / 4,545 kgs
	Towing Capacity 1st Gear*	130,000 lbs / 58,967 kgs
	Towing Capacity 3rd Gear*	60,000 lbs / 27,273 kgs
	Service Weight Gas	
	Service Weight Diesel	17,000 lbs / 7,711 kgs
DIMENSIONS	Length	208 in / 5,283 mm
	Width	101in / 2,565 mm
	Height	96in / 2,438 mm
	Wheelbase	112 in / 2,845 mm
	Track	Front - 80 in / 2,032 mm    Rear - 71 in / 1,803 mm
	Tires (front & rear)	11R22.5
	Turn Radius (outside)	203 in / 5,156 mm
	Step Height	16 in / 406 mm
	Ground Clearance	10 in / 254 mm
	CHASSIS	Frame/Body
Bumper (front/rear)		1.0 in (25 mm) / 1.0 in (25 mm) steel
Suspension		Springs and shock absorbers over each axle
TRAVEL	Transmission – Automatic	5 forward / 1 reverse
	Max Speed Governed	25 mph
	Steering	Hydraulic power-boosted mechanical: self-centering
	Brakes	Hydraulic, self-adjusting split type with accumulator
	Front Brakes	Disc
	Rear Brakes	Disc
	Parking Brake	Foot or lever activated - mechanical to rear brake drum (pinion mounted)
<b>ENGINE OPTIONS</b>		<b>EB2-10 DIESEL</b>
SPECIFICATIONS	Manufacturer	Cummins - Tier 4
	Model	ISB I-6 Turbo
	Rated Output	Up to 325 hp / 242 kW
	Torque	Up to 750 ft-lbs
	Cylinders - Displacement	Six - 6.7L
	Fuel Consumption	3.3 gph
	Fuel Tank	45 gal / 170 lit
Air Cleaner	Severe environment, heavy duty, dry replacement element	
ELECTRICAL	System	12 Volt
	Alternator	185 amp
	Battery (cold crank)	(2) 625 CCA
	Ignition	Keyed
	Lights	Halogen headlights / combination brake, tail and back-up
Instruments	Oil pressure, water temperature and fuel gauges / hourmeter, voltmeter and electric horn	

\* Normal Operating Conditions - Wet, 1% grade.

**SOLD & SERVICED BY:**